

WATERPROOFING SOLUTIONS

ISSUE 8 | WPDOP05

DECLARATION OF PERFORMANCE : CM20 CAVITY DRAIN MEMBRANE

1 . PRODUCT NAME

CM20 CAVITY DRAIN MEMBRANE

2. INTENDED USES

Waterproofing sheet for damp proof sheets, Type V, BS EN 13967 : 2012 + A1 2017

3. NAME, REGISTERED TRADE NAME

Wykamol Group Ltd, Unit 3 Boran Court, Network 65 Business Park, Hapton, Burnley, BB11 5TH, United Kingdom

4. AVCP

System 2+

5. HARMONISED STANDARD

BS EN 13967 : 2012 + A1 :2017

6. NOTIFIED BODIES

0809

7. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TEST STANDARD	HARMONISED TECHNICAL SPECIFICATION
Water tightness, 60 kPa; 24h	Pass	EN 1928	
Resistance to tearing	MD - npd CMD - npd	EN 12310-1	
Elongation (5%)	MD - npd CMD - npd	EN 12311-2	
Compressive creep (resistance to static load)	npd	EN 13967 Annex B	
Impact Resistance	npd	EN12691-2 Method A	EN 13967 : 2012 + A1 : 2017
Durability against ageing	npd	EN 1296/ EN 1928	
Durability against chemicals	npd	EN 1296/ EN 1928	
Fire resistance	E	EN 13501-1:2007 +A1:2009	
Joint tensile shear resistance	npd	EN 12317-2	
Compressive strength	170 kN/m ²	BS EN ISO 25619-2	

WATERPROOFING SOLUTIONS

ISSUE 8 | WPDOP05

DECLARATION OF PERFORMANCE : CM20 CAVITY DRAIN MEMBRANE

8 . DECLARATION

The performance of the product identified above is in conformity with the declared performance/s.
The declaration of this performance is issued under the sole responsibility of the manufacturer identified above.
A digital copy of this Declaration of Conformity can be found on the Wykamol website - www.wykamol.com.

Signed for and on behalf of the manufacturer by:

Name: Nicholas Street
Operations Director

Place and Date of Issue: Burnley, 2021 01

Signature:

